

## VALTTI NON-SLIP

<b>DESCRIPTION</b>	Coarse water-borne wood oil for outdoor use. Wood oil protects against moisture and dirt, and reduces surface cracking. The product includes non-slip agents to increase surface grip.
<b>EXAMPLES OF USE</b>	Terraces, jetties and wooden steps.
<b>SUITABILITY</b>	Protects exterior wooden surfaces. Suitable for impregnated (pressure-treated), heat-treated and untreated wood, as well as wood previously treated with oil.
<b>TECHNICAL DATA</b>	
<b>Base paint</b>	EP
<b>Colours</b>	Colourless. Tinted according to the Translucent Wood Finishes colour card.
<b>Gloss grade</b>	Not defined.
<b>Coverage</b>	8–12 m <sup>2</sup> /l, depending on the porosity of the surface.
<b>Can size</b>	2.7 l and 9 l
<b>Thinner</b>	Water.
<b>Application</b>	Brush.
<b>Tool cleaning</b>	Wash with soap and water. We recommend removing partially hardened wood oil with Tikkurila Pensselipesu (Tool cleaner).
<b>Drying time, +23 °C air relative humidity RH 50 %</b>	Surface dries in several hours under normal conditions.
<b>Resistance</b>	We recommend tinting the product to provide better weather resistance than colourless paint.  Use Maintenance Cleaner if necessary.
<b>Solids volume</b>	25 %.
<b>EU VOC 2004/42/EC limit value</b>	(cat A/e) 130 g/l (2010)
<b>Density</b>	1,0 kg/l, ISO 2811.
<b>Storage</b>	Protect from frost. Once opened, use up the product during the same work project, in half-empty cans product characteristics may vary.

# VALTTI NON-SLIP

## INSTRUCTIONS

**Application conditions** The surface to be treated must be dry and relative wood moisture content less than 20 %, as damp wood will not absorb oil, which dries slowly. As impregnated wood is often damp, we recommend treatment after a 6-month drying period.

During treatment and drying, air, surface, and product temperature must be at least +5 ° C and relative air moisture less than 80%.

## Pretreatment

### Untreated surfaces:

Remove all dirt, dust and loose material from the surface. Wash off mould with Homeenpoisto (Mould Removal) or Tehopesu (Super Clean) according to instructions.

### Surface previously treated with translucent finishing:

Remove loose material from the surfaces with a scraper or wire brush. Clean and wash if necessary with Homeenpoisto (Mould Removal) or Tehopesu (Super Clean) according to instructions. If a clear, possibly glossy film remains on the surface, remove it with a pressure washer or sand it down carefully.

## Application

Stir Valtti Non-Slip oil thoroughly before and during use. To avoid overlapping, apply two thin coats of oil in continuous strokes to cover the whole surface evenly.

Carry out maintenance if necessary. Surfaces continuously exposed to the weather may need to be treated annually.

## Maintenance

After application, the surface must be treated gently for the first week to allow it to harden completely. After two days, gently clean the surface with a soft brush or mop if necessary.

Clean dirty surfaces with Tikkurila Huoltopesu Maintenance Cleaner (1 part of Maintenance Cleaner to 10 parts water). Remove stains and clean very dirty surfaces with a stronger solution of Maintenance Cleaner (1:1). After washing, rinse the surfaces and allow to dry.

## HEALTH AND SAFETY CLASSIFICATION

according to EC Directive 99/45/EC

Not classified as hazardous to health.

A Material Safety Data Sheet is available on request.

## ENVIRONMENTAL

Empty cans should be recycled or disposed of in accordance with local regulations. Liquid waste should be destroyed according to the local regulations.

Risk of self-ignition! Cleaning cloths or sanding dust containing the product can create fire by self-ignition and should therefore be stored in water before disposal, or dried outdoors or incinerated immediately.

## TRANSPORT CLASSIFICATION

ADR/RID not classified

dco091008/ome141008/581 6404-