



UNIT B3  
SOUTH GYLE CRESCENT LANE  
EDINBURGH EH12 9EG

TEL: +44 (0)131 334 4999  
FAX: +44 (0)131 334 3987  
EMAIL: [enquiries@valtti.co.uk](mailto:enquiries@valtti.co.uk)

[www.valtti.co.uk](http://www.valtti.co.uk)

## VALTTI FILLER STOPPER

### DESCRIPTION

Quick drying alkyd filler for interior and exterior use which is easily sanded down.

### EXAMPLES OF USE

For filling cracks, joints, nail holes, indentations, etc., on wood, building boards and metal surfaces. Filler Stopper can be used to fill bare, primed or painted surfaces.

### TECHNICAL DATA

Solids Volume: approx. 74%

Density: 1.8 kg/l ISO2811

Thinner White Spirit 1050

Application method Spatula or spray

### Colour Range

White

### SPECIFICATIONS

#### Preparation

Surfaces must be clean, dry and free from dirt, oil, wax, rust, all loose material and surface contamination. Ensure that all glossy surfaces are thoroughly flatted down prior to filling. Better adhesion will be achieved by priming porous surfaces prior to filling.

#### Filling Conditions

The surface to be filled must be dry, the temperature of the air at least +5°C, and the relative humidity of the air at least 80%.

#### Filling

Apply with putty knife or spreader. On larger cracks, holes or defects some sinkage may occur and it may be necessary to apply a second application of Filler Stopper. When dry, Filler Stopper can be wet- or dry-sanded prior to priming or painting.

#### Drying Times

At 23°C and 50% relative humidity of the air: normally dry in ½ hour to 2 hours depending upon the layer thickness.

#### Cleaning of Tools

Remove excess filler from tools and clean with white spirit.

### ENVIRONMENTAL

Avoid spillage into drains, water systems and soil. Empty cans should be recycled or disposed of in accordance with local regulations. Product waste should be destroyed according to the local regulations for hazardous waste.

### HEALTH AND SAFETY CLASSIFICATION

according to EC Directive 99/45/EC

Contains: Naphtha, hydrodesulfurized heavy FLAMMABLE. HARMFUL TO AQUATIC ORGANISMS, MAY CAUSE LONG-TERM ADVERSE EFFECTS IN THE AQUATIC ENVIRONMENT. Use only in well ventilated areas. If swallowed, seek medical advice immediately and show this container or label. Do not empty into drains. Keep out of the reach of children. Contains methylethylketoxime. May produce an allergic reaction. A Material Safety Data Sheet is available at request. [Material Safety Data Sheet - Lakkakitti](#)



UNIT B3  
SOUTH GYLE CRESCENT LANE  
EDINBURGH EH12 9EG

TEL: +44 (0)131 334 4999  
FAX: +44 (0)131 334 3987  
EMAIL: [enquiries@valtti.co.uk](mailto:enquiries@valtti.co.uk)  
[www.valtti.co.uk](http://www.valtti.co.uk)

**TRANSPORT  
CLASSIFICATION**

ADR/RID -